




NAUTILUS® Classic combines the authentic recycled paper shade with the stringent Blue Angel environmental profile. This 100% recycled paper is optimized for trouble free printing and copying. Send a visible environmental message at first glance.



Technical Data: NAUTILUS® CLASSIC

			70	80	90	100	120	160
Basis weight	g/m ²	ISO 536	70 ± 2.5	80 ± 3.0	90 ± 3.0	100 ± 3.0	120 ± 4.0	160 ± 4.0
Caliper	µm	ISO 534	92 ± 3	104 ± 3	116 ± 3	127 ± 4	159 ± 4	214 ± 5
Roughness Bendtsen	ml/min	ISO 8791-2	220 ± 50	220 ± 50	220 ± 50	220 ± 50	220 ± 50	220 ± 50
Opacity	%	ISO 2471	93.5 ± 1	94.0 ± 1	96.0 ± 1	97.0 ± 1	98.0 ± 1	99.0 ± 1
Moisture abs.	%	ISO 287	4.6 ± .6	4.6 ± .6	4.6 ± .6	4.6 ± .6	4.6 ± .6	5.2 ± .6
Brightness UV	%	ISO 2470	88.0 ± 3.0	88.0 ± 3.0	88.0 ± 3.0	88.0 ± 3.0	88.0 ± 3.0	88.0 ± 3.0
CIE Whiteness	%	ISO 11475	112 ± 3.0	112 ± 3.0	112 ± 3.0	112 ± 3.0	112 ± 3.0	112 ± 3.0

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and DIN6738, ageing resistance. Production processes are certified according to ISO 9001, ISO 14001 and OHSAS 18001. Standard measurement uncertainty between laboratories is not incorporated.

SIGNIFICANCE OF VALUES: 2 SIGMA

This specification is valid for one year after issue or good till cancelled.

250	300
250 ± 5.0	300 ± 8.0
318 ± 4	380 ± 8
220 ± 50	220 ± 50
100.0	100.0
5.2 ± .5	5.2 ± .5
88.0 ± 3.0	88.0 ± 3.0
112 ± 3.0	112 ± 3.0



NAUTILUS® Classic combines the authentic recycled paper shade with the stringent Blue Angel environmental profile. This 100% recycled paper is optimized for trouble free printing and copying. Send a visible environmental message at first glance.



Technical Data: NAUTILUS® CLASSIC Office

Basis weight	g/m ²	ISO 536
Caliper	µm	ISO 534
Roughness Bendtsen	ml/min	ISO 8791-2
Opacity	%	ISO 2471
Moisture abs.	%	ISO 287
Brightness UV	%	ISO 2470
CIE Whiteness	%	ISO 11475

80
80 ± 3.0
104 ± 3
220 ± 50
94.0 ± 1
4.6 ± .6
88.0 ± 3.0
112 ± 3.0

Product meets EN 12281, requirements for copy paper for dry toner imaging processes and DIN6738, ageing resistance. Production processes are certified according to ISO 9001, ISO 14001 and OHSAS 18001. Standard measurement uncertainty between laboratories is not incorporated.

SIGNIFICANCE OF VALUES: 2 SIGMA

This specification is valid for one year after issue or good till cancelled.

