

UPM DIGI COLOR LASER

Woodfree uncoated supercalendered paper specially designed for high quality digital printing. It has an extra smooth surface and a high whiteness, providing brilliant and sharp images with vibrant colours. For the ultimate in stunning images, brilliant colors, subtle color nuances and perfect contrast.

UPM DIGI COLOR LASER:

| Category | Office papers |
|-------------------------|--|
| Grade | Woodfree uncoated (WFU) |
| End use | Advertising material Colour diagrams Correspondence Direct mailing Documents Flyers High-quality documents Leaflets Manuals Memos Newsletters Office applications Product data sheets Reports Transactional / transpromotional documents |
| Finish | Supercalendered |
| Printing method | B/W laser printing (dry toner) Colour laser printing (dry toner) |
| Format/Size | A3 A4 |
| Wrapping | Strong kraft paper Strong moisture proof polyethylene laminated kraft paper |
| Certificates and labels | EMAS EU Ecolabel FSC Chain-of-Custody ISO 14001 ISO 50001 ISO 9001 OHSAS 18001 Permanent Paper ISO 9706 |
| Note | FSC® certified. 80 g/m² available upon request. |

TECHNICAL TARGET VALUES:

| Basis Weight (ISO 536) (g/m²) | 90.0 | 100.0 | 120.0 | 160.0 | 250.0 |
|--|-------|-------|-------|-------|-------|
| Brightness D65 (ISO 2470-2) (%) | 114.0 | 114.0 | 114.0 | 114.0 | 114.0 |
| CIE Whiteness (%) | 170.0 | 170.0 | 170.0 | 170.0 | 170.0 |
| Opacity ISO (2471) (%) | 93.5 | 95.0 | 97.0 | 99.0 | 99.7 |
| Smoothness PPS 10 (ISO 8791-4) (μm) | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 |
| Roughness Bendtsen (ISO 8791-2) (ml/min) | 50.0 | 50.0 | 50.0 | 50.0 | 50.0 |
| Thickness (ISO 534) (μm) | 95.0 | 105.0 | 126.0 | 168.0 | 263.0 |

Please note: Technical values are informative and subject to production variations.